


SIGMA

SLIM STREET LIGHT

60W



Brightman™
design efficiency



TECHNICAL DATA


SIGMA SLIM STREET LIGHT 60W

Input Voltage	AC100-277V ~ 47/63 Hz
LED Chips	Nichia
Driver	Inventronics
LED Power	60W
Led Luminous Efficiency	140lm/W
Luminous Flux	8,400lm
Power Factor	>0.95
Colour Temperature	4500~5500K (2500~5500K optional)
Colour Rendering Index	Ra≥75
Beam Angle	75° x 150°
Illuminance Design	LED+lens
Working Temperature	-20°C ~ 50°C
Working Humidity	15%~ 90% RH
IP Rating	IP65
Net weight	2.5Kg
Life-span	>50,000hrs
Power Cable	1.0mm ² Triple shield wire
Connection Wire	Brown=Live, Blue=Neutral, Yellow=Earth
Housing Material	Die Cast Aluminum
Housing Colour	Dark Grey or Silver Grey
Mounting Options	Pole or Surface
Optional Extras	Daylight Sensor



DIMENSIONS

SIGMA SLIM STREET LIGHT 60W



OPTIONAL DAYLIGHT SENSOR



Increased savings and reduce your carbon footprint with automdimming sensors